

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7: H01M 12/06, 2/10, H04M 1/02, H01M 6/50

A2

(11) International Publication Number:

WO 00/36690

(43) International Publication Date:

22 June 2000 (22.06.00)

(21) International Application Number:

PCT/US99/28425

(22) International Filing Date:

1 December 1999 (01.12.99)

(30) Priority Data:

60/112,292	15 December 1998 (15.12.98)	US
60/119,563	10 February 1999 (10.02.99)	US
60/119,568	10 February 1999 (10.02.99)	US
09/293,927	15 April 1999 (15.04.99)	US
60/135,061	20 May 1999 (20.05.99)	US

(71) Applicant (for all designated States except US): ELECTRIC FUEL LIMITED [IL/IL]; Western Industrial Park, P. O. Box 641, 99000 Bet Shemesh (IL).

(72) Inventors; and

- (75) Inventors/Applicants (for US only): SHRIM, Yaron [IL/IL]; 20/1 Mazel Shor Street, Jerusalem (IL). GIVON, Menachem [IL/IL]; Kibutz Shoval, DN Hanegev (IL). ROSENBERG, Tzvi [IL/IL]; 1 Hashikmah Street, Mevaseret Tziyon (IL). DOPP, Robert, B. [US/US]; 1925 Fields Pond Glen, Marietta, GA 30068 (US).
- (74) Agent: LYON & LYON LLP; Mark A. Catan, 633 West fifth Street, Suite 4700, Los Angeles, CA 90071-2066 (US).

(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published

Without international search report and to be republished upon receipt of that report.

RECEIVED


JUL - 5 2000

LYON & LYON INT'L. PROSECUTION

(54) Title: BATTERY PACK DESIGN FOR METAL-AIR BATTERY CELLS

(57) Abstract

capacity (single-use; primary non-rechargeable) battery pack for high current portable appliances as cellular phones employs electrochemical cells that use ambient oxygen for one of the electrodes. The pack makes possible a simple low cost design by providing for oxygen supply in a completely passive yet compact configuration. provide for compactness while providing the high gas



exchange rates required of high current devices in a passive air management design, a variety of design tactics are developed and applied in various embodiments. Many types of disposable cells are not rechargeable and can cause dangerous problems in appliances that contain hands-free adapters or chargers, such as cell phones. A protective device is disclosed which either limits charging to the degree that charging can be accepted or prevents charging entirely. Various mechanisms for achieving this result are disclosed.